



earthship.com

Earthship Store

Shurflo 3GPM 24vDC water pump

\$145.95



SHURflo 2088 Series diaphragm pumps deliver reliable performance in high flow, moderate pressure applications. They are used in a variety of transfer and dispense-on demand applications where flow to 3.6 GPM is required. For added reliability the Twist-on Strainer can be used on the 2088 inlet port. Install optional 4" or 5" heatsink for heavy duty applications where extra cooling is required.

Features

- Self priming up to 12 feet
- Can run dry without damage
- Optional motor cooling fins
- One way check valve prevents reverse flow
- Available for 12 VDC, 24 VDC, and 115 VAC
- Automatic operation with pressure demand switch

Specifications*

SHURflo Model: 2088-474-144

Description:	3.0 GPM open flow, Santoprene® valves, Santoprene® diaphragm, 45 PSI Demand Switch, 1/2" MSPT ports (1/2" - 14 National American Straight Pipe Thread, requires SHURflo swivel type fittings), Poly Housing			
Voltage:	24 VDC			
PSI:	10	20	30	40
BAR:	0.7	1.4	2.1	2.8
GPM:	2.80	2.25	1.75	1.25
L/min:	10.6	8.5	6.6	4.7
Amps:	2.41	2.63	2.73	2.71

*Specifications subject to change.

[Vendor Information](#)

Customer Reviews: There are yet no reviews for this product.
Please log in to write a review.